Chenfeny HYDRAULIC MACHINE

HYDRAULIC CUTTING MACHINE



CF-405
HYDRAULIC SWING ARM
CUTTING PRESS

CF-405 HYDRAULIC SWING ARM CUTTING PRESS

This machine is suitable for cutting leather, card board, fabric plastic, rubber, asbestos, cork, felt, cellophane etc., because of fully hydraulic operation and light alloy arm ensure maximum pressure granteed and maximum protection to the cutting knives and a noiseless vibration free cutting.

To set the press in motion the operator must use both hands for positive safety. The stroke end automatic adjustment for different height of cutting knives, easy operation simple maintenance and seldom breakdown.

SPECIFICATION

MODEL TEHCNICAL DATA	CF-405A	CF-405B	CF-405B-1	CF-405C
Pressure	15 Tons.	20 Tons.	20 Tons.	25 Tons.
Stroke	0~3.54 in.	$0 \sim 3.54$ in.	0~3.54 in.	0~3.54 in.
Cutting Pad Area	35.4×17 in.	39×19.6 in.	39×19.6 in.	39×19.6 in.
Pressing Plate Area	14.5 × 21.6 in.	14.5 × 21.6 in.	21.6×21.6 in	21.6 × 21.6 in.
Height of cutting knife	0.8~2 in.	0.8~2 in.	0.8~2 in.	0.8~2 in.
Motor Power	$2\text{HP} \times 6\text{P}$	$2\text{HP} \times 6\text{P}$	2HP × 6P	$3\text{HP} \times 4\text{P}$
Hydraulic Oil	60 Liters	65 Liters	65 Liters	65 Liters
Size $(W \times D \times H)$	$35.4 \times 39 \times 51$ in.	$39 \times 39 \times 51$ in.	$39 \times 39 \times 51$ in.	$39 \times 39 \times 51$ in.
N.W.	2200 Lbs.	2420 Lbs.	2464 Lbs.	2464 Lbs.
G.W.	2530 Lbs.	2750 Lbs.	2794 Lbs.	2794 Lbs.

The description and features mentioned on the catalogues are not binding any change maybe made without notice.



AGENT: